

REC'D 07 JAN 2005

WIPO PCT

PCT/SG2004/000424

**REGISTRY OF PATENTS
SINGAPORE**


This is to certify that the annexed is a true copy of following application as filed with the Registry.

Date of Filing : 13 FEB 2004


Application Number : 200400668-0

Applicant(s) /
Proprietor(s) of Patent : SO, KIM LUI

Title of Invention : SELF CLEANING FILTER ASSEMBLY


Chig Kam Tack (Mr)
Senior Assistant Registrar
for REGISTRAR OF PATENTS
SINGAPORE

03 Jan 2005



**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

BEST AVAILABLE COPY

21

Common Form Index

Entry Date : 13-Feb-2004 18:19:18

Classification : Normal

Classification : Confidential

Examination Date : 13-Feb-2004

Remarks :

Receipt No : 91380

General Indexes

Our Reference : BLUE/20400227/KC/MT

Title of Invention : SELF CLEANING FILTER ASSEMBLY

Number of Applicants

Number of applicants : 1

Details of Applicant

Name : SO, KIM LUI

Address : BLK 3, NORMANTON PARK

16-173, SINGAPORE 119000

Nationality :

Country : SG

Date of incorporation :

Country of incorporation :

Date of residency :

Country of residency : SG

Others :

Declaration of Priority

Country or Country Designated :

Serial number :

Filing date :

Inventor

Applicants are inventors : Yes

Form 8 is or will be furnished : No

Claiming an earlier filing date under

Section :

Patent application number :

Filing date :

Proceeding under :

Date on which earlier application was amended :

Section 14(4)(c) Requirements

The invention has been displayed at an international exhibition : No

Section 114 Requirements

The invention relates to and/or used a microorganism deposited for the purposes of

Disclosure in accordance with section 114 with depository authority under the Budapest Treaty : No

Checklist (A) The application consists of the following number of sheets

Request :

Description without Claims :

Description with Claims : 17

Drawings : 10

Abstract : 1

Total number of sheets (B) The application as filed is accompanied by : 28

Priority documents : No

Inventorship statement : No

Translation of Priority Documents : No

International Exhibition Certificate : No

Details of Agent

Name :

Firm : ALBAN TAY MAHTANI & DE SILVA

Address for Service in Singapore

Block or House No :

Level No :

Unit No or PO Box : 0

Street Name :

Building Name : RAFFLES CITY POST OFFICE

Postal Code : 911722

Patents Form 26 is or will be furnished

Patents Form 26 is or will be furnished :

Printed : 03-Jan-2005

SELF CLEANING FILTER ASSEMBLY

1

Field of the Invention

- 5 The present invention relates to a self-cleaning filter assembly and refers particularly, though not exclusively, to a self-cleaning filter assembly for use in domestic and industrial exhaust systems for exhausting vapours such as, for example, vapours produced by cooking in kitchens and chemical processes.

Background to the Invention

It is mandatory in many industries to employ exhaust systems for removing contaminated air from affected work areas. Examples of such industries are the manufacturing and chemical industries.

15

Such exhaust systems are commonly employed in kitchens such as industrial and commercial kitchens in the food processing industry, and restaurants. Whenever food is cooked, it is common for the food to be cooked using oil. As such, cooking creates fumes which contain oil droplets.

20

- Filters that are installed within such exhaust systems usually comprise a steel mesh to capture the majority of oil droplets. Such filters may be located in the exhaust hood, the flue of the exhaust hood, or in the ducting. Droplets which are not captured by the filter may end up coating the internal surfaces of the exhaust hood, the flue, and the ducting. When these oil droplets cool and start to dry they become very sticky, and are hard to remove. Some of these droplets that do not coat the internal walls of the exhaust system may be expelled into the atmosphere, contributing to air pollution. Other problems that may arise are: shortened exhaust fan life span due to clogging by contaminants, a rapid build-up of bacteria in the internal walls of the exhaust system leading to a compromise of hygiene; increased fire risk from a dried grease layer along the internal walls; and workplace ventilation problems resulting from ineffective exhaust operation.
- 25
- 30

The filters employed in such exhaust systems have fairly open mesh patterns as having too fine a mesh pattern would cause each filter to be easily clogged, leading to minimised system effectiveness, and increase in system downtime due to frequent filter maintenance and cleaning. Such maintenance sessions are time-consuming, tedious, and labour intensive task. As such, it is usually not a cheap process.

There have been many proposals for self cleaning exhaust systems using water curtains, water baths, or sprays. However, most are one or more of: complex, large, expensive, ineffective, dangerous to use.

Summary of the Invention

There is provided a self cleaning filter assembly for use in an exhaust system, including: a casing for placement in the path of an air flow, the casing containing: a first filter; a second filter; a barrier for placement adjacent to the casing to prevent a cleaning fluid from dripping from the first filter and out from the casing; and a plurality of spray outlets for dispersion of fluid within the casing and onto the filters. The plurality of spray outlets create droplets of the cleaning fluid of a size able to combine with droplets of a contaminant to form combined droplets in the air flow and wherein the first filter and the second filter captures droplets of the contaminant and droplets from the spray outlets.

The barrier may be a plurality of louvres that creates openings when the exhaust system is operational. The plurality of louvres may be fixed in a particular orientation. Alternatively, the barrier is slidable into the casing to create an opening when the exhaust system is operational.

Advantageously, the barrier includes baffles to retard the air flow. Preferably, the barrier includes at least one chamber for the containment of fluid. It is preferable that there is a conduit for fluid drainage in the at least one chamber.

It is preferable that each spray outlet disperses fluid with an arc of between sixty degrees and one hundred eighty degrees. It is more preferable that each spray outlet disperses fluid with an arc of ninety degrees. It is desirable for each spray outlet to be a nozzle.

5

Preferably, the cleaning fluid includes water and a degreaser in a required ratio in the range 1:10 to 1:50. The plurality of spray outlets may be on an inlet side of a filter selected from the group consisting of the first filter and the second filter. The plurality of spray outlets may be located at each edge of a filter selected from the group consisting of the first filter and the second filter. The plurality of spray outlets may be located at the middle portion of each side of a filter selected from the group consisting of the first filter and the second filter. The plurality of spray outlets may also be located on opposed corners of a filter selected from the group consisting of the first filter and the second filter.

15

It is preferable that the plurality of spray outlets are located within the casing. It is advantageous that the barrier comprises at least one chamber with at least one baffle therein.

20 **Description of the Drawings**

In order that the invention can be readily understood and put into practical effect, there shall now be described by way of non-limitative example only a preferred embodiment of the present invention, the description being with reference to the accompanying illustrative drawings in which:

25

Figure 1 shows a side view of the self cleaning filter assembly of a preferred embodiment of the present invention with louvres at an "open" position;

Figure 2 shows a side view of an alternative embodiment of the self cleaning filter assembly of the present invention with louvres at an "open" position.

30

Figure 3 shows the front view of the nozzle arrangement in Figure 1;

Figure 4 shows a front view of a second filter of the self cleaning filter assembly of the present invention with a second arrangement of spray outlets;

Figure 5 shows a front view of a second filter of the self cleaning filter assembly of the present invention with a third arrangement of spray outlets;

Figure 6 shows a front view of a second filter of the self cleaning filter assembly of the present invention with a fourth arrangement of spray outlets;

5 Figure 7 shows a side view of the self cleaning filter assembly of the present invention employed in an exhaust system;

Figure 8 shows the front view of the nozzle arrangement in Figure 2;

Figure 9 shows a front view of a first filter of the self cleaning filter assembly of the alternative embodiment of the present invention with a second arrangement of
10 spray outlets;

Figure 10 shows a front view of a first filter of the self cleaning filter assembly of the alternative embodiment of the present invention with a third arrangement of spray outlets;

Figure 11 shows a front view of a first filter of the self cleaning filter assembly of the
15 alternative embodiment of the present invention with a fourth arrangement of spray outlets;

Figure 12 shows a side view of the self cleaning filter assembly of the alternative embodiment of the present invention employed in an exhaust system;

Figure 13 shows a side view of the self cleaning filter assembly of the present
20 invention with louvres at an "close" position; and

Figure 14 shows a preferred embodiment of the present invention employed into an existing exhaust hood system.

Description of the Preferred Embodiments

25

To first refer to Figure 1, there is shown an airflow path through an exhaust system in which air flows in the direction of arrow 50. The air flowing in the direction of arrow 50 may contain contaminants such as, for example, oil droplets, dust, particulate matter and the like. Air is drawn in the direction of arrow 50 when an
30 exhaust fan (not shown) of the exhaust system is in operation.

A self cleaning filter assembly 52 is mounted in an airflow path in the exhaust system along the direction 50 of airflow. The self cleaning filter assembly may be

adaptable to fit braces or slots of existing filter assemblies in existing exhaust systems. Existing baffle filters may be replaced by the self cleaning filter assembly 52. This may enable a conventional kitchen exhaust system to be converted into an advanced grease removal kitchen exhaust system with minimal capital outlay. This is shown in Figure 14. The self cleaning filter assembly 52 may be fitted in existing braces or slots in an existing exhaust system 120.

The self cleaning filter assembly 52 includes a casing 54. The casing 54 may be a peripheral case bordering close to the internal walls of the pathways of the exhaust system. The filter assembly 52 should substantially block the pathway so that only a minimal volume of air does not pass through the filter assembly 52. A first filter 56 and a second filter 62 are located within the casing 54 in the path of airflow for filtering contaminants such as, for example, oil droplets, dust, particulate matter and the like, from the air flowing in direction 50.

Located before a first end 53 of the casing 54 is an additional fixture 55 comprising a first chamber 57, a second chamber 58, baffles 59, and an adjustable set of louvres 60. The louvres 60 may be activated when the exhaust fan is in operation. The louvres 60 may also be activated when there is sufficiently fast air flow. The fixture 55 may be attached to the casing 54 or may be attached to the internal walls of the pathways of the exhaust system. Figure 1 shows the instance when the exhaust fan may be operational and the louvres 60 are in an "open" position. Air is then able to flow into openings 63 created by the open louvres 60. When louvres 60 are in the closed position, openings 63 are also closed. However, the louvres 60 may be non-adjustable and locked in a fixed orientation. As such, openings 63 may always be present. Figure 13 shows the louvres 60 in a "closed" position.

When the exhaust fan is not operational, cleaning of filters in the filter assembly 52 may still be carried out with the louvres 60 in a "closed" position. The edges of each louvre 60 may be lined with water-tight sealing material such as, for example, silicone, rubber and the like. As such, cleaning solution does not leak from the filter assembly 52 into other portions of the exhaust system and areas to be ventilated. This prevents leakage into areas to be ventilated, such as, for example, kitchens,

clean rooms and the like. Besides employing louvres 60, a shutter-door like assembly may be used to allow airflow into the filter assembly 52 and to block cleaning solution from exiting from the filter assembly 52. The first chamber 57 and the second chamber 58 of the fixture 55 may also be employed to contain the cleaning solution with drainage in each chamber being drained by a conduit for fluid 64, such as, for example, a drainage pipe.

Located behind the first filter 56 is a second filter 62 preferably substantially the same as first filter 56, so as to allow for inter-changeability. The mesh size of the second filter 62 may be the same as first filter 56, or may be smaller. The first filter 56 may be a relatively coarse filter while the second filter 62 may be a relatively fine filter. Alternatively, the first filter 56 may be relatively fine, and the second filter 62 may be relatively coarse. The baffles 59 in the fixture 55 may aid in retarding the speed of air flow through the filter assembly 52 and to prevent spray 68 from exiting through opening 63, particularly when the exhaust fan is not in operation. Such an arrangement may allow for some contaminants to be removed by the first filter 56, with the second filter 62 used for capturing even smaller contaminants. In such an arrangement, the risk of clogging both the first filter 56 and the second filter 62 is significantly reduced. The first filter 56 may prevent fluid sprayed from nozzles 66 and 70 from exiting the opening 63 of the filter assembly 52. The second filter 62 may also prevent fluid sprayed from nozzles 66 and 70 from exiting the rear end 100 of the filter assembly 52. This minimises the down-time of the exhaust system and may also lower maintenance costs. The filtration rating and type of each filter may be determined by the type of contaminant to be removed from the air flow.

A cleaning solution basin or tank (not shown) may be operatively connected to the filter assembly 52. The tank may be attachable to the exhaust system or may be incorporated in the exhaust system. If separate, appropriate connections such as by hoses, tubes, pipes, manifolds, and so forth will need to be provided. Located in or adjacent the tank may be a pump for optionally supplying a cleaning solution through pipes, tubes or hoses to a first nozzle 66 located in between the first filter 56 and the second filter 62. Nozzle 66 may be a single nozzle, a plurality of nozzles

in an array, an outlet manifold with a plurality of holes (as in a shower rose), or the like.

The purpose of nozzle 66 is to provide a fine spray 68 of water that may contain cleaning solution into the airflow onto the first filter 56 and onto a front surface 69 of the second filter 62 so that the air flow drawn by the exhaust fan draws the fine spray 68 onto substantially the front surface 69 of the second filter 62. The nozzle 66 "atomizes" the cleaning solution to form a fine spray 68. The nozzle 66 may disperse the cleaning solution over an arc of between sixty and one hundred eighty degrees. Preferably, the nozzle 66 disperses the cleaning solution with an arc of ninety degrees. A second nozzle 70 may also be located in the filter assembly 52 between the first filter 56 and the second filter 62 for the same purpose as the first nozzle 66.

Figure 3 shows the front view of the nozzle arrangement as shown in Figures 1. The first nozzle 66 and a second nozzle 70 are located in front of front surface 69 of the second filter 62. The second nozzle 70 may be the same as first nozzle 66, or maybe different. The first nozzle 66 and second nozzle 70 each disperse cleaning solution in a fine spray 68 with an arc of ninety degrees, allowing coating of a substantial portion of the front surface 69 of second filter 62 with cleaning solution. Coating the front surface 69 of second filter 62 may improve the adhesive properties of the second filter 62 for capturing contaminants from the airflow 50. Figure 4 shows an alternative arrangement of two nozzles that each disperse cleaning solution in a fine spray 68 with an arc of one hundred eighty degrees such that a substantial portion of the front surface 69 of second filter 62 is coated with cleaning solution. Figures 5 and 6 show alternative arrangements of four nozzles. Figure 5 shows nozzles that each disperse cleaning solution in a fine spray 68 with an arc of ninety degrees while Figure 6 shows nozzles that each disperse cleaning solution in a fine spray 68 with an arc of one hundred eighty degrees. A single nozzle may also be sufficient for the task of coating a substantial portion of the front surface 69 of second filter 62 with cleaning solution; as is the deployment of a number of nozzles that are not specifically mentioned in the description. A separate pump may be used for each nozzle or, they may all be connected to a single pump.

Referring to Figure 7, the spray 68 should have a droplet size such that it will be carried by the airflow onto surface 69 of second filter 69. However, the pressure applied to each nozzle should preferably not so great that spray 68 will be reflected
5 off surface 69 with such force that it will be flow against the airflow and thus risk passing along the airpath into other portions of the exhaust system. By having filter assembly 52 in an angled position, any excess spray will tend to be captured in the chambers 57, 58 and drained by the conduit 64 for recycling. Consequently, the amount of cleaning solution required is also reduced. However, when louvres 60
10 are in "closed" position, the pressure of the spray 68 may be greater to force contaminants off the filters 56, 62.

In this way the second filter 62 is cleaned by spray 68. The spray 68 will also combine with the contaminants in the airflow to form larger droplets. Louvres 60
15 may be coated with polytetrafluoroethylene (PTFE or commercially known as Teflon) for ease of removal of such hardened droplets during maintenance. Hence, the louvres 60 may also aid in the filtration process.

Also, the larger droplets will more likely be captured by second filter 62. When
20 captured by second filter 62, as the oil droplets are still fluid as they have not yet cooled, they will be acted on by the degreaser in the cleaning solution of spray 68, and will thus flow down second filter 62 under the influence of gravity to the bottom of casing 54, and flow through an opening into chambers 57, 58. In this way the cleaning solution may be recycled as oil droplets in the waste tank will rise to the
25 top facilitating separation of the cleaning solution while the oil may be collected for disposal or recycling.

The spray 68 coats a substantial portion of the front surface 69 of the second filter 62, thus enhancing the capturing of contaminants by the second filter 62. Under the
30 influence of the airflow, and the spray 68 simultaneously coats and flushes all surfaces of the second filter 68.

In this way the majority of contaminants and cleaning spray 68 is captured by filters 62, 56. This prevents the majority of contaminants and the cleaning spray passing along subsequent portions of the exhaust system. This prevents damage to duct linings, exhaust fans and other components of the exhaust system.

5

Figure 2 shows an alternative embodiment of the present invention. There is shown an airflow path through an exhaust system in which air flows in the direction of arrow 20. The air flowing in the direction of arrow 20 may contain contaminants such as, for example, oil droplets, dust, particulate matter and the like. Air is drawn in the direction of arrow 20 when an exhaust fan (not shown) of the exhaust system is in operation.

A self cleaning filter assembly 22 is mounted in an airflow path in the exhaust system along the direction 20 of airflow. The self cleaning filter assembly 22 may be adaptable to fit braces or slots of existing filter assemblies in existing exhaust systems. The self cleaning filter assembly includes a casing 24. The casing 24 may be a peripheral case bordering close to the internal walls of the pathways of the exhaust system. The filter assembly 22 should substantially block the pathway so that only a minimal volume of air does not pass through the filter assembly 22. A first filter 26 is located within the casing 24 in the path of airflow for filtering contaminants such as, for example, oil droplets, dust, particulate matter and the like, from the air flowing in direction 20.

Located before a first end 23 of the casing 24 is an adjustable set of louvres 30 that are activated when the exhaust fan is in operation. The set of louvres 30 may be attached to the casing 24 or may be attached to the internal walls of the pathways of the exhaust system. Figure 2 shows the instance when the exhaust fan is operational and the louvres 30 are in an "open" position. The louvres 30 may also be activated when there is sufficiently fast air flow. Air is then able to flow into openings 21 created by the open louvres 30. When the exhaust fan is not operational, cleaning of filters in the filter assembly 22 may still be carried out with the louvres 30 in a "closed" position. The edges of each louver 30 are also lined with water-tight sealing material such as, for example, silicone, rubber and the like.

As such, the cleaning solution does not leak from the filter assembly 22 into other portions of the exhaust system and areas to be ventilated. This prevents leakage into areas to be ventilated, such as, for example, kitchens, clean rooms and the like. Besides employing louvres 30, a shutter-door like assembly may be used to allow airflow into the filter assembly 22 and to block cleaning solution from exiting from the filter assembly 22. However, the louvres 30 may be non-adjustable and locked in a fixed orientation. As such, openings 21 may always be present.

Located behind the first filter 26 is a second filter 28 preferably substantially the same as first filter 26, so as to allow for inter-changeability. Its mesh size may be the same as first filter 26, or may preferably be smaller. The first filter 26 may be a relatively coarse filter while the second filter 28 may be a relatively fine filter. Such an arrangement may allow for the majority of contaminants to be removed by the first filter 26, with the second filter 28 used for capturing even smaller contaminants. In such an arrangement, the risk of clogging both the first filter 26 and the second filter 28 is significantly reduced. This minimises the down-time of the exhaust system and may also lower maintenance costs. The filtration rating and type of each filter may be determined by the type of contaminant to be removed from the air flow.

A cleaning solution basin or tank (not shown) may be operatively connected to the filter assembly 22. The tank may be attachable to the exhaust system or may be incorporated in the exhaust system. If separate, appropriate connections such as by hoses, tubes, pipes, manifolds, and so forth will need to be provided. Located in or adjacent the tank may be a pump for optionally supplying a cleaning solution through pipes, tubes or hoses to a first nozzle 32 located in front of first filter 26. Nozzle 32 may be a single nozzle, a plurality of nozzles in an array, an outlet manifold with a plurality of holes (as in a shower rose), or the like.

The purpose of nozzle 32 is to provide a fine spray 34 of water that may contain cleaning solution into the airflow in front of front surface 36 of first filter 26 so that the air flow drawn by the exhaust fan draws the fine spray 34 onto substantially the complete front surface 36 of the first filter 26. The nozzle 32 "atomizes" the cleaning

solution to form a fine spray 34. The nozzle 32 disperses the cleaning solution over an arc of between sixty and one hundred eighty degrees. Preferably, the nozzle 32 disperses the cleaning solution with an arc of ninety degrees.

- 5 Figure 8 shows the front view of the nozzle arrangement as shown in Figure 2. The first nozzle 32 and a second nozzle 38 are located in front of front surface 36 of the first filter 26. The second nozzle 38 may be the same as first nozzle 32, or maybe different. The first nozzle 32 and second nozzle 38 each disperse cleaning solution in a fine spray 34 with an arc of ninety degrees, allowing coating of a substantial portion of the front surface 36 of first filter 26 with cleaning solution. Coating the front surface 36 of first filter 26 may improve the adhesive properties of the first filter 26 for capturing contaminants from the airflow. Figure 9 shows an alternative arrangement of two nozzles that each disperse cleaning solution in a fine spray 34 with an arc of one hundred eighty degrees such that a substantial portion of the front surface 36 of first filter 26 is coated with cleaning solution. Figures 10 and 11 show alternative arrangements of four nozzles. Figure 10 shows nozzles that each disperse cleaning solution in a fine spray 34 with an arc of ninety degrees while Figure 11 shows nozzles that each disperse cleaning solution in a fine spray 34 with an arc of one hundred eighty degrees. A single nozzle may also be sufficient for the task of coating a substantial portion of the front surface 36 of first filter 26 with cleaning solution; as is the deployment of a number of nozzles that are not specifically mentioned in the description. A separate pump may be used for each nozzle or, they may all be connected to a single pump.
- 25 Referring to Figure 12, the spray 34 should have a droplet size such that it will be carried by the airflow onto surface 36 of first filter 26. However, the pressure applied to each nozzle should preferably not so great that spray 34 will be reflected off surface 36 with such force that it will be flow against the airflow and thus risk passing along the airpath into other portions of the exhaust system. By having filter assembly 22 in an angled position, any reflected spray will tend to be captured by the airflow and directed onto surface 36 of first filter 26. The airflow is being used to assist the fine spray 34 onto surface 36 of first filter 26, However, when louvres 30
- 30

are in "closed" position, the pressure of the spray 34 may be greater to force contaminants off the filter 26.

5 The cleaning solution may be water or, preferably, the cleaning solution is a mixture of water and a degreaser in a required ratio. The ratio may be any suitable ratio depending on the degreaser used, and the type of contaminant being filtered. For example, filtration of cooking fumes and chemical fumes would require different constituent percentage parts of the cleaning solution. Preferably the ratio is in the range of 1:10 to 1:50; more preferably 1:20. For example, if the contaminants are
10 acidic the cleaning solution may be alkaline to not only capture and clean, but also to neutralize the contaminants. Similarly, for alkaline contaminants, the cleaning solution may be acidic. For gaseous contaminants, the cleaning solution may contain neutralizing solutions and/or gases.

15 In this way the first filter 26 is cleaned by spray 34. The spray 34 will also combine with the contaminants in the airflow to form larger droplets. The larger droplets will tend to fall from the airflow before contacting first filter 26 and will drop under the influence of gravity to the bottom of a pathway 110. The larger droplets may also adhere to the surfaces of louvres 30. Louvres 30 may be coated with
20 polytetrafluoroethylene (PTFE or commercially known as Teflon) for ease of removal of such hardened droplets during maintenance. Hence, the louvres 30 may also aid in the filtration process.

Also, the larger droplets will more likely be captured by first filter 26. When
25 captured by first filter 26, as the oil droplets are still fluid as they have not yet cooled, they will be acted on by the degreaser in the cleaning solution of spray 34, and will thus flow down first filter 26 under the influence of gravity to the bottom of casing 24, and flow through an opening into a waste tank in the exhaust system. In this way the cleaning solution may be recycled as oil droplets in the waste tank will
30 rise to the top facilitating separation of the cleaning solution while the oil may be collected for disposal or recycling.

The spray 34 coats a substantial portion of the front surface 36 of the first filter 26, thus enhancing the capturing of contaminants by the first filter 26. By having the spray 34 in front of the first filter 26, the spray 34 is continuously drawn to, into, and through the first filter 26 under the influence of the airflow, and thus simultaneously coats and flushes all surfaces of the first filter 26.

Droplets from spray 34, particularly relatively fine droplets, and smaller than usual contaminants may pass through first filter 26. They would then be carried by the airflow to second filter 28. At least one nozzle may also be positioned between the first filter 26 and the second filter 28 to substantially coat a front surface 110 of the second filter 28 with cleaning solution for the identical purpose as first filter 26.

In this way the majority of contaminants and cleaning spray 34 is captured by filters 26, 28. This prevents the majority of contaminants and the cleaning spray passing along subsequent portions of the exhaust system. This prevents damage to duct linings, exhaust fans and other components of the exhaust system.

The louvres 30 may be in the same circuit as the exhaust fan for the airflow such that the louvres 30 are in the "closed" position when the exhaust fan is not operational. Hence, the spraying of cleaning solution will take place even when there is no airflow. In this way the cleaning solution cannot flow to the other parts of the exhaust system and the area to be ventilated. However, the louvres 30 should be able to be independently controlled, if desired. This may be required to enable cleaning of the louvres. The pump may also be in the same circuit as the exhaust fan such that sprays from the at least one nozzle may be drawn towards the filters and will not fall under the influence of gravity.

The louvres 30 may also be operable dependent on the speed of the air flow in pathway 110 in the exhaust system. An anemometer (not shown) may be installed into the pathway 110 of the exhaust system to measure the speed of the air flow such that the louvres 30 may be automatically positioned to the "open" position if the speed of the air flow exceeds a specific amount. Similarly, the louvres 30 may

be automatically positioned to the "closed" position if the speed of the air flow is of a negligible value, as this means that there is no activity in the area to be ventilated.

- 5 By having filters 26, 28 continuously cleaned during the operation of the exhaust system, clogging is less likely and thus smaller mesh sizes may be used in filters 26, 28 to thus increase the effectiveness of their operation. The risk of fire from dried contaminants is also considerably minimised.
- 10 Whilst there has been described in the foregoing description preferred embodiments of the present invention, it will be understood by those skilled in the technologies concerned that variations in details of design or construction may be made without departing from the present invention.
- 15 The present invention extends to all features disclosed either individually, or in all possible combinations and permutations.

Claims

1. A self cleaning filter assembly for use in an exhaust system, including:
a casing for placement in the path of an air flow, the casing containing:
5 a first filter;
a second filter;
a barrier for placement adjacent to the casing to prevent a cleaning
fluid from dripping from the first filter and out from the casing; and
a plurality of spray outlets for dispersion of fluid within the casing and onto
10 the filters,
wherein the plurality of spray outlets create droplets of the cleaning fluid of a
size able to combine with droplets of a contaminant to form combined droplets in
the air flow and wherein the first filter and the second filter captures droplets of the
contaminant and droplets from the spray outlets.
15
2. A self cleaning filter assembly as claimed in claim 1, wherein the barrier is a
plurality of louvers that creates openings when the exhaust system is operational.
3. A self cleaning filter assembly as claimed in claim 1, wherein the barrier is
20 slidable into the casing to create an opening when the exhaust system is
operational.
4. A self cleaning filter assembly as claimed in any one of claims 1 to 3,
wherein the barrier includes baffles to retard the air flow.
25
5. A self cleaning filter assembly as claimed in any one of claims 1 to 4,
wherein the barrier includes at least one chamber for the containment of fluid.
6. A self cleaning filter assembly as claimed in claim 5, wherein there is a
30 conduit for fluid drainage in the at least one chamber.

7. A self cleaning filter assembly as claimed in any one of claims 1 to 6, wherein each spray outlet disperses fluid with an arc of between sixty degrees and one hundred eighty degrees.

5 8. A self cleaning filter assembly as claimed in claim 7, wherein each spray outlet disperses fluid with an arc of ninety degrees.

9. A self cleaning filter assembly as claimed in any one of claims 1 to 8, wherein each spray outlet is a nozzle.

10

10. A self cleaning filter assembly as claimed in any one of claims 1 to 9, wherein the cleaning fluid includes water and a degreaser in a required ratio in the range 1:10 to 1:50.

15 11. A self cleaning filter assembly as claimed in any one of claims 1 to 10, wherein the plurality of spray outlets are on an inlet side of a filter selected from the group consisting of: first filter and second filter.

12. A self cleaning filter assembly as claimed claim 11, wherein the plurality of
20 spray outlets are located at each edge of a filter selected from the group consisting of: first filter and second filter.

13. A self cleaning filter assembly as claimed in any one of claims 1 to 10, wherein the plurality of spray outlets are located at the middle portion of each side
25 of a filter selected from the group consisting of: first filter and second filter.

14. A self cleaning filter assembly as claimed in any one of claims 1 to 10, wherein the plurality of spray outlets are located on opposed corners of a filter selected from the group consisting of: first filter and second filter.

30

15. A self cleaning filter assembly as claimed in any one of claims 1 to 14, wherein the plurality of spray outlets are located within the casing.

16. A self cleaning filter assembly as claimed in any one of claims 1 to 15, wherein the barrier comprises at least one chamber with at least one baffle therein.

17. A self cleaning filter assembly as claimed in claim 2, wherein the plurality of
5 louvres are fixed in a particular orientation.

Abstract**SELF CLEANING FILTER ASSEMBLY**


5 There is provided a self cleaning filter assembly for use in an exhaust system. The filter assembly includes a casing for placement in the path of an air flow. The casing contains a first filter, a second filter, a barrier means for placement adjacent to the casing to prevent a cleaning fluid from dripping from the first filter and out from the casing when the exhaust system is not operational, and a plurality of spray outlets
10 for dispersion of fluid within the casing and onto the filters. The plurality of spray outlets create droplets of the cleaning fluid of a size able to combine with droplets of a contaminant to form combined droplets in the air flow and wherein the first filter is and the second filter captures droplets of the contaminant and droplets from the spray outlets.




15

Fig. 7

Fig

2/10





4/10




Fig 6

5/10







Fig 7



7/10




Fig 11 .

8/10




Fig 12

9/10




Fig 13

10/10




Fig 14

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.